

This document contains proprietary information and such information may not be disclosed to others for any purposes, not used for sales/marketing/procurement purposes without written permission

REV	DESCRIPTION OF REVISION	ECN NO.	BY	DATE	APPROVED
A	Initial Release	—	H.wei	19/03/17	19/03/17

**Electrical**


- 1.1 Impedance: 50Ω
- 1.2 Frequency: DC-18GHz
- 1.3 VSWR: 1.20~1.45
- 1.4 Power Rating: 100W@25°C
- 1.5 Temperature range: -55°C ~ +125°C
- 1.6 Attenuator Range: 6~60dB

Frequency & V.S.W.R Range

Frequency Range	VSWR
DC ~4GHz	1.20:1
DC ~8GHz	1.25:1
DC ~12.4GHz	1.35:1
DC ~18GHz	1.45:1

Standard Nominal Values and Deviations

Attenuator Value(dB)	Accuracy(dB)			
	DC ~4GHz	DC ~8GHz	DC ~12.4GHz	DC ~18GHz
6~10	0.7	0.8	0.9	1.5
20	0.7	0.8	0.9	1.5
30	0.8	0.9	1.0	1.3
40	0.8	0.9	1.0	1.3
50~60	0.9~1.0	1.0	1.1	1.4





Tel: Lee13890694956

Web: www.hltchips.com

**Notes:**

- 1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME
- 2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: H.wei 19/03/17	TITLE:	
ENGINEER: L.yu 19/03/17	Precision Adapter	
APPROVED: W.yi 19/03/17	N Male to Female Attenuator	
TOLERANCES UNLESS OTHERWISE SPECIFIED		 DIMENSION IN MILLIMETERS (mm)
X ±0.50 .X ±0.20 .XX ±0.10 ANGLES ±1°		
PART NO: HL-NMF-100-18-XX	SIZE: A4	SCALE: N/A
	SHEET: 1/1	REV: A